



Submittal / Spec sheet



COARSE THREAD DRYWALL SCREWS

“Gripper” Bugle Head Coarse Thread sharp point screws

Part #	Diam.	Length	Count	Head	Head Diam	Finish	Corrosion	Thread length	Point
60012CB	6	6x1/2	25m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60034CB	6	6x3/4	15m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60100CB	6	6x1	10m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60118CB	6	6x1-1/8	10m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60114CB	6	6x1-1/4	8m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60158CB	6	6x1-5/8	5m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60200CB	6	6x2	3.5m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
60214CB	6	6x2-1/4	3m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
70200CB	7	7x2	3.5m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
80200CB	8	8x2	3.5m	Bugle	8.0~8.5M	Phos	48hr min B117	Full	pierce
80212CB	8	8x2-1/2	2.5m	Bugle	8.0~8.5M	Phos	48hr min B117	50	pierce
80300CB	8	8x3	2m	Bugle	8.0~8.5M	Phos	48hr min B117	50	pierce

Description: Bugle Head, #2 reduced Philips, coarse thread sharp point wood screws. Phosphate coated. Meets or exceeds ASTM C-1002.

Application: For attaching drywall or wood to wood. 1/2” and 5/8” single layer drywall to wood. 1/2” and multi-layer drywall (Gypsum Board) to wood. Plywood, OSB or other woods to wood.

Directions for use: Installation Guidelines: Use a 0-4000 rpm adjustable Torque Screw-gun . Caution: Overdriving may result in fastener failure or strip-out of the Substrate. The fastener is fully seated when the head’s bearing surface is flush with the drywall or attached item.

Certifications: All Pro-Plus Screws are manufactured in a Certified and approved ISO9001 Factory.