



Submittal / Spec sheet



Bugle Head Fine Thread Drill point screws

Part #	Diam.	Length	Count	Head	Head Diam	Finish	Corrosion	Drill Cap Min #	Drill Cap Max #	Point
60118DB	6	1-1/8	10M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
60114DB	6	1-1/4	8M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
60158DB	6	1-5/8	5M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
60178DB	6	1-7/8	4M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
80238DB	8	2-3/8	2.5M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
80300DB	8	3	2M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill
60114DZ	8	1-1/4	8M	Bugle	8.0~8.5M	Phos	48hr min B117	22 ga.	12 ga.	Drill

Description: Bugle head, #2 reduced tip Philips drive fine thread drywall screws. Phosphate coated. Meets or exceeds ASTM C-954 and/or ASTM C-1513.

Application: For attaching drywall or wood to light gauge steel. 22-12ga. 1/2” and 5/8” single layer drywall to metal studs and track. 1/2” and multi-layer drywall (Gypsum Board) to light gauge steel studs and track. Plywood and or OSB to light gauge steel.

Directions for use: Installation Guidelines 0-2500 rpm adjustable Torque Screw-gun and depth gauge. Caution: - Over-driving may result in fastener failure or strip-out of the work surface. The fastener is fully seated when the head’s bearing surface is flush with the drywall.

Certifications: All Pro-Plus Screws are manufactured in a Certified and approved ISO9001 Factory.