



“Preferred by Professionals”™



Submittal / Spec sheet



FRAMING SCREWS

Hex / Round Washer / Beveled Truss Head Drill point screws

Part #	Diam.	Length	Count	Head	Head Diam	Finish	Corrosion	Drill Cap Min #	Drill Cap Max #	Point
80012DWZ	8	8x1/2	10M	RWH	10.5~11.0mm	Zinc	24hr min B117	20 ga.	16 ga.	Drill
80916SWZ	8	8X9/16	10M	RWH	10.5~11.0mm	Zinc	24hr min B118	26 ga.	20 ga.	Sharp
80114DWZ	8	8x1-1/4	5M	RWH	10.5~11.0mm	Zinc	24hr min B117	20 ga.	16 ga.	Drill
80114SWZ	8	8X1-1/4	5M	RWH	10.5~11.0mm	Zinc	24hr min B118	26 ga.	20 ga.	Sharp
10034DHZ	10	10x3/4	7M	HWH	10.0~11.0mm	Zinc	24hr min B117	20 ga.	14ga.	Drill
12034DHZ	12	12x3/4	5M	HWH	12.2~13.2mm	Zinc	24hr min B117	20 ga.	12 ga.	Drill
12100DHZ	12	12x1	3M	HWH	12.2~13.2mm	Zinc	24hr min B117	20 ga.	12 ga.	Drill
10034DBTZ	10	10x3/4	7.5M	BTH	9.07~9.47	Zinc	24hr min B117	20 ga.	14 ga	Drill

Description: Round Washer Head, Hex head, and Beveled Truss Head. reduced tip Philips drive fine thread drywall screws. Zinc coated. Meets or exceeds ASTM C-954 and/or ASTM C-1513.

Application: For attaching light gauge steel to steel. 20-12ga. IE: Sheet metal to metal studs and track.

Directions for use: Installation Guidelines: Use a 0-2500 rpm adjustable Torque Screw-gun . Caution: Overdriving may result in fastener failure or strip-out of the work surface. The fastener is fully seated when the head's bearing surface is flush with the initial metal. Installed fasteners must penetrate the substrate metal by at least 3 threads.

Certifications: All Pro-Plus Screws are manufactured in a Certified and approved ISO9001 Factory.